

SLIPGrip[®]

Safety Tape Primer



DESIGN

SUPPLY

FABRICATE

INSTALL



SlipGrip Anti Slip Tape Primer for applying safety tapes on poor surfaces, this primer will give a better adhesion and thus extend the life of the tape.

500ml

SUITABLE SUBSTRATES

- ✓ Wood
- ✓ Concrete
- ✓ Stone
- ✓ Metal

APPLICATION

- ✓ Simply stir and brush on with a 1 - 2 inch paint brush.
- ✓ Make sure you only apply the primer to areas that the products will cover, otherwise dust may settle on exposed primer.
- ✓ NB: This product should not be used in wet environments.
- ✓ After application, brushes can be washed out in water.

TECHNICAL DATA

Coverage:	500ml tin is sufficient for 2 – 3m ² 1 tin covers 1 x 18m x 150mm anti slip tape roll or 2 x 18m x 50mm anti slip tape rolls.
Drying time:	Dries in one a hour at 10-15°C
Colour:	Applied milky, dries clear.
Classification of the substance or mixture	Product defintion: Mixture Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] Eye Irrit. 2, H319 Classification according to Directive 1999/45/EC [DPD] This product is not classified as dangerous according to Directive 1999/45/EC and its amendments.



These instructions are to be used as a guide. Always employ safe practices. It is recommended to first test the suitability of any product on a small area before carrying out a full application.

LABEL ELEMENTS

Date of issue/Date of revision:	17/03/2015
Date of previous issue:	No previous validation
Version:	1 1/11
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - United Kingdom (UK) Safety Tape Primer - Resin	

PERSONAL PROTECTION EQUIPMENT

Wear protective gloves and eye protection: nitrile rubber gloves and safety glasses with side shields.



WARNING - CAN CAUSE SERIOUS EYE IRRITATION

Keep out of reach of children. Read label before use. If medical advice is needed, have product container or label at hand. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: seek medical attention.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Anti Slip Tape Primer	Anti Slip Tape Sealer
This is ideal for porous or dusty surfaces. Simply stir and brush on. Coverage is 2-3m ² per 500ml. The appearance when applied is milky, but it dries (in about one hour at 10-15°C) clear. Make sure you only apply the primer to areas that the products will cover, otherwise dust could settle on exposed primer. After application, brushes can be washed out in water.	If you are using the products where moisture could penetrate the tape edge, or in very heavily-trafficked areas , then we recommend you apply our Anti Slip Tape Sealer. All you need to do is squeeze the sealer from the tube around the tape edge. This will give extra protection and increase the tape's life.



Southern Office:
Unit 2, Civic Industrial Estate,
Homefield Road Central,
Haverhill,
Suffolk,
CB9 8QP



Northern Office:
Kingston House,
3 Walton Road,
Pattinson North,
Washington,
Tyne & Wear,
NE38 8QA



www.fibregrid.com



Email: sales@fibregrid.com



Phone: 01440 712722



**SPECIALITY
PRODUCTS** Brand



001