

SLIPGrip[®]

Anti Slip Roll On Flooring



DESIGN

SUPPLY

FABRICATE

INSTALL



Our SlipGrip® Anti Slip Roll On Flooring is made from aluminium oxide grit, which makes them long-lasting and anti slip.

There are two finishes - coarse and fine. The choice of which is determined by level of foot traffic. There are also two lengths - 1m x 4.5m or 1m x 9.1m; for small or large projects.

CHARACTERISTICS

- Easy application with self-adhesive backing - simply peel back the adhesive backing and roll down onto the preferred surface
- Long-lasting due to a strong resin-bonded aluminium oxide anti slip grit
- Water resistant and pressure sensitive
- Compliant with Building Regulations and Disability Discrimination Act (DDA) 2005

SUITABLE APPLICATIONS

- ✓ Interior and exterior applications
- ✓ Industrial environments
- ✓ Commercial environments
- ✓ Domestic environments

SUITABLE SUBSTRATES

- ✓ Wood
- ✓ Concrete
- ✓ Metal
- ✓ Stone



PREPARATION

- ✓ Ensure that the area is clean, dry, smooth and free from loose and friable material.
- ✓ If your surface is non-porous and dust free, priming should not be necessary. However, dusty/porous surfaces should be primed with our Anti Slip Tape Primer.



These installation instructions are to be used as a guide. Always employ safe practices. It is recommended to first test the suitability of any fixing method on a small area before carrying out a full installation programme.

APPLICATION

1. 	Peel off the backing strip to a length of approx. 50mm, which gives you more control than if you peel off too much. Then, firm the product into place with a hand or foot. Take care not to stretch the roll. If you find you've made a mistake, don't worry as this can be peeled off easily immediately after fitting, but ensure you do this straight away.
2. 	If you are fitting onto surfaces that may get wet, or are likely to experience heavy traffic, then we recommend you use our Anti Slip Tape Edge Sealer.

Anti Slip Tape Primer

This is ideal for porous or dusty surfaces - simply stir and brush on. Coverage is 2-3m² per 500ml. The appearance when being applied is milky, but it dries clear (in about 1 hour at 10-15°C).

Make sure you only apply the primer to areas that the products will cover, otherwise dust could settle on exposed primer.

After application, brushes can be washed in water.

Anti Slip Tape Sealer

If you are using the products where moisture could penetrate the tape edge, or in very heavily-trafficked areas, we recommend you apply our Anti Slip Tape Sealer. Squeeze the sealer from the tube around the tape edge, this will provide extra protection and increase the tape's service life.

Downtime

Although these products can be walked on immediately, full adhesion takes 24 hours, so please take care with them during this period and avoid heavy use.

Storage

Keep the product warm and dry before use.



Southern Office:
Unit 2, Civic Industrial Estate,
Homefield Road Central,
Haverhill,
Suffolk,
CB9 8QP



Northern Office:
Kingston House,
3 Walton Road,
Pattinson North,
Washington,
Tyne & Wear,
NE38 8QA



www.fibregrid.com



Email: sales@fibregrid.com



Phone: 01440 712722



001