

SLIPGrip[®]

Line Marking Paint



DESIGN

SUPPLY

FABRICATE

INSTALL



To paint demarcation lines on concrete or asphalt. in car parks or school playgrounds, for example, you need a specialist paint for the job. Our SlipGrip® line marker is based on a chlorinated rubber blend and so can withstand wear from tyres or feet on a regular basis.

It is also formulated to withstand a slightly damp environment, will resist showers after only an hour, and can even be applied at 0°C.

CHARACTERISTICS

- Long-lasting - its chlorinated rubber blend means it can withstand high levels of vehicle or foot traffic in both internal and external environments
- Versatile application - our line marking paint can be applied at temperatures as low as 0°C and is rain-proof within one hour of applying, able to withstand pedestrian traffic within 4 hours (at 10°C)
- One coat application
- Brushes wash out easily
- Applicable to slightly damp areas
- Suitable for interior and exterior applications
- Suitable for light to medium traffic

SUITABLE APPLICATIONS

- Private roads
- Car parks
- Industrial floors
- School playgrounds

SUITABLE SUBSTRATES

- Bare concrete
- Asphalt
- Painted floors
- Aged blacktop
- Thermoplastic coverings
- Over previously painted lines



TECHNICAL DATA

Coverage:	12-15m ² per 5L tin
Colour:	White
Applicators:	Best applied using a 2"-3" paint brush or mini roller
Coat amount:	One coat needed

PREPARATION

- ✓ Ensure surface is clean, dry, and free from wax, oil, food residue or any other substance likely to affect the application of the paint. Grease and oil should be removed with our SlipGrip® Standard Degreaser.
- ✓ Previously painted surfaces should be roughened slightly using sanding material. New concrete should be left at least 28 days before applying the paint.
- ✓ No primer is required, however if you are applying to concrete, and you feel the surface needs a more smooth, porous key, you can apply our SlipGrip® Concrete Keying Etchant to neutralise any remaining alkalinity in the cement and to remove further dirt and laitance (weak, dusty cement particles).
- ✓ We also recommend patch testing a small trial area first in areas where appearance is critical.

APPLICATION

<p>1.</p> 	<p>It is always advisable to test a small area of any new product to ensure you are happy with the appearance.</p> <p>Simply paint on with a roller or brush.</p>
<p>2.</p> 	<p>Drying times:</p> <p>Shower proof in a minimum of 30 minutes at 23°C or 60 minutes at 10°C.</p> <p>Touch dry in a minimum of 40 minutes at 10°C and 90 minutes at 0°C.</p> <p>Walk on after a minimum of 2 hours at 20°C, 4 hours at 10°C and 8 hours at 0°C.</p> <p>As ever, drying times are increased by lower temperatures.</p>
<p>Note: SlipGrip® Line Marker dries quickly, so ensure the lid is kept on the tin when not in use.</p>	



These installation instructions are to be used as a guide. Always employ safe practices. It is recommended to first test the suitability of any product on a small area before carrying out a full application.

SAFETY

Store container in a well-ventilated place. If using indoors, ensure the area being painted has adequate ventilation.

Do not smoke near this product and keep it away from sources of ignition.

Avoid skin contact and wear protective clothing and gloves.

STORAGE

This product is highly flammable with a flash point below 21°C.

Store in a cool, dry and well-ventilated place.

SHELF LIFE

12 months if unopened.

TOOL CLEANING

Use a Xylene solvent based thinner and cleaner.

LIMITATIONS

This product contains Xylene and is not recommended for use indoors or on sensitive decorative surfaces.

If in doubt, apply to a small test area. Also test before using on painted floors.

WASTE DISPOSAL

Both material and container should be disposed of as hazardous waste.

If in doubt, call us on 01440 712722 for expert friendly advice.



Southern Office:
Unit 2, Civic Industrial Estate,
Homefield Road Central,
Haverhill,
Suffolk,
CB9 8QP



Northern Office:
Kingston House,
3 Walton Road,
Pattinson North,
Washington,
Tyne & Wear,
NE38 8QA



www.fibregrid.com



Email: sales@fibregrid.com



Phone: 01440 712722



001